

SMART PARTS

Washable, Reusable Cabin Air Filters

INSTALLATION INSTRUCTIONS PART NO. SP11746

The cabin air filter is located in front of windshield on passenger side under cowl vent screen
Installation time: 45 min

- Lift windshield wipers to vertical position. Remove by turning counterclockwise the retaining clips at base of arms. Hold retaining clip outward, lift and remove wiper arms. (FIG 1)
- Remove six screws at base of windshield (FIG 2)
- Open hood, locate and remove four plastic screws along the forward edge of cowl vent screen (FIG 3, 4)
- Remove four screw anchors by pushing upward on screw anchors (FIG 5)
- Lift cowl vent screen, locate and disconnect the windshield wiper hose at the Y connector (FIG 6)
- Carefully lift and remove the cowl vent screen (FIG 7, 8)
- On passenger side, locate and remove four screws which secure cabin air filter access cover FIG 9)
- Remove the filter cover (FIG 10)
- Remove the old filter and frame (FIG 11)
- Install new Smart Parts Washable Reusable Cabin Air Filter (squeeze to fit if needed)
- Reverse above steps to reassemble



Figure 1



Figure 2



Figure 3




Figure 4



Figure 5



Figure 6



Figure 7



Figure 8



Figure 9




Figure 10



Figure 11



Figure 12

This is only a guide. See Owner's Manual and/or your mechanic for exact instructions for your particular model.